

PRODUCT INFORMATION

DESCRIPTION

Polyzane Removal Gel is a carefully formulated gel which allows for easy removal of the PZP coatings on painted and vinyl surfaces without affecting the paint or vinyl.

The use of Polyzane Removal Gel allows for areas that may have been damaged to be repaired simply and easily.

APPLICATION INFORMATION

APPLICATION

Brush or roller.

Ensure any glass surfaces are completely covered up using vinyl or sheeting.

The gel must not be applied to glass surfaces. For best results apply generously to the area requiring removal using a brush or roller ensuring all areas to be removed are coated.

Leave the gel on the surface for 2-4 hours ensuring the gel remains wet on the surface. For full application instructions and H&S please email info@polyzane.com

CLEAN DOWN

Dispose of all tools after use.

TECHNICAL INFORMATION

UV:	Stable
Consistency:	Gel
Appearance:	Clear / Colorless liquid
Container size:	5L
Binder base:	Water
Compatibility:	Painted surfaces, vinyl (Always apply a patch test)

COLOUR

Green / blue colour

SURFACES

GRP, composite materials, metals, aluminium, stainless steel, non-absorbent surfaces. NOT GLASS.

STORAGE

Shelf life 18 months. Store at temperatures between 5°C - 24°C. DO NOT ALLOW LIQUID TO FREEZE and do not store in direct sunlight.

PRODUCT PROPERTIES

- SAFELY REMOVES PZP CERAMIC COATINGS
- WATER BASED
- EASILY & SAFELY STORED

GET IN TOUCH

info@polyzane.com
www.polyzane.com
+44(0) 843 289 6780

71-75 Sheton Street
Covent Garden
London, WC2H 9JQ